WBS ELEMENT:	EFF. 01-15-02
DIVISION: COUNTY:	REV. 07-05-05
LETTING DATE:	

REVIEW LIST FOR FINAL RESURFACING PLANS LET UNDER THE 2002 SPECIFICATIONS		
EET UNDER THE 2002 STEETTCATIONS		
PLACE "CHECK MARK" BY APPLICABLE ITEMS ON THIS REVIEW LIST PLACE "NA" BY NON-APPLICABLE ITEMS ON THIS REVIEW LIST		
<u>MAPS</u>		
 . DOES EACH SECTION DESCRIPTION AGREE WITH LIMITS SHOWN ON MAP? . ARE ROUTE NUMBERS CORRECT ON PLAN SHEETS? . IS MILEAGE FOR EACH SECTION SHOWN CORRECTLY? . DO MAPS HAVE NORTH ARROWS, CITY AND COUNTY NAMES? . PLACE MAPS ON 11" X 17" SHEETS. 		
TYPICAL SECTIONS		
 DO TYPICAL SECTIONS REPRESENT THE INTENDED CONSTRUCTION? (ie, ARE EXISTING DITCHES BEING MOVED, SHOULDERS ADDED, ETC.?) DOES PROPOSED RESURFACING PAVEMENT WIDTH OF EACH SECTION AGREE WITH TYPICAL SECTIONS? DOES "RESURFACING SCHEDULE" SHOW CORRECT MATERIAL TYPES AND APPLICATION RATES? DEPTHS ARE NOT SHOWN EXCEPT FOR MILLING. IF THERE IS SHOULDER CONSTRUCTION, A SHOULDER WIDTH SHOULD BE SHOWN ON THE TYPICAL SECTION. SEE PROJECT SPECIAL PROVISIONS (RESURFACING LINEUP SHEET) FOR MEASUREMENT AND PAYMENT OF THIS ITEM. IF THERE IS MILLING, TYPICAL SECTIONS SHOULD INDICATE THIS. IF A TYPICAL SECTION APPLIES EXCEPT FOR MILLING ON SOME OF THE MAPS, INDICATE BY NOTE WHICH MAPS HAVE MILLING. LABEL SHOULDER RECONSTRUCTION AND/OR SHOULDER CONSTRUCTION ON TYPICAL SECTIONS, IF APPLICABLE. 		
QUANTITIES		
 ARE THE QUANTITIES FOR SURFACE COURSE, INTERMEDIATE COURSE, OF BASE COURSE CORRECT WITH APPROPRIATE PERCENTAGE INCREASE (TO ACCOUNT FOR MAILBOX TURNOUTS, DRIVES, ETC.) AS DIRECTED BY DIVISION? IF QUANTITY APPEARS TO BE IN ERROR AND THERE ARE NO ACCOMPANYING QUANTITY CALCULATIONS, CALL DIVISION AND RESOLVE DISCREPANCY. IS ASPHALT BINDER FOR PLANT MIX QUANTITIES CORRECT? 		

ASPHALT BINDER FOR LEVELING COURSE SHOULD BE INCLUDED;

D	HOWEVER, ASPHALT BINDER FOR PATCHING MATERIAL WILL NOT. DO PLANS, SPECIFICATIONS, AND ESTIMATES ADDRESS THE NUMBER OF NEW "WHEELCHAIR RAMPS" AND/OR "RETROFIT EXISTING WHEELCHAIR RAMPS" WITH TRUNCATED DOMES.
A	ARE ITEMS SUCH AS ADJUSTMENT OF MANHOLES, METER AND VALVE BOXES CORRECT ON SUMMARY OF QUANTITIES?
IS	S A QUANTITY OF ASPHALT SURFACE TREATMENT TO BE INCLUDED? IF SO, SEE PROJECT SPECIAL PROVISION CONCERNING MEASUREMENT AND PAY ITEMS. NOTE: ASPHALT BINDER FOR PLANT MIX IS NOT USED IN CONJUNCTION WITH AST.
<u>DETAILS</u>	
	S DETAIL OF BRIDGE HALF TYPICAL SECTION SHOWN ON PLANS, IF APPLICABLE?
	S A DETAIL FOR ASPHALT CONCRETE SURFACE COURSE (LEVELING
	COURSE) SHOWN ON PLANS, IF APPLICABLE?
	S A DETAIL FOR PATCHING EXISTING PAVEMENT SHOWN ON PLANS, IF APPLICABLE?
	ARE ANY SPECIAL DETAILS SHOWN ON PLANS WHEN APPLICABLE?
ESTIMAT	<u>`E</u>
(A	F THERE IS WEDGING OF EXISTING PAVEMENT OR A LEVELING COURSE, QUANTITIES SHOULD BE SEPARATED FOR EACH TYPE: S9.5, S12.5, ETC. A SEPARATE PAY ITEM IS REQUIRED FOR EACH TYPE OF PAVING MATERIAL ARE WBS ELEMENTS CORRECTLY SHOWN ON ESTIMATE? STHE COUNTY NAME(S) SHOWN CORRECTLY?
IS	S THE PAY ITEM NUMBER, SECTION NUMBER, AND ITEM DESCRIPTION CORRECT AND APPLICABLE?
D	OO THE UNITS AND QUANTITIES CORRESPOND TO THOSE ON THE
	SUMMARY OF QUANTITIES? S MILEAGE SHOWN CORRECTLY?
II	F PAVEMENT REPAIR IS REQUIRED, QUANTITY SHOULD BE IDENTIFIED AS "PATCHING EXISTING PAVEMENT", A SPECIAL PAY ITEM DISCUSSED IN THE PROJECT SPECIAL PROVISIONS.
D	DESCRIPTION ON ESTIMATE SHOULD INDICATE ALL TYPES OF WORK
	NVOLVED; i.e. MILLING, RESURFACING, WIDENING, SHOULDER
	CONSTRUCTION, ETC. THE NUMBER OF SECONDARY AND PRIMARY ROADS SHOULD BE INDICATED. ALL PRIMARY ROADS SHOULD BE
	SPECIFICALLY IDENTIFIED BY ROUTE AND ALL "SR" ROADS SHALL BE
	DENTIFIED AS SECONDARY ROADS (EXAMPLE: 2 SECTIONS OF US-64,
	SECTION OF US-70, AND 20 SECTIONS OF SECONDARY ROADS). THE
	TOTAL NUMBER OF SECTIONS SHOULD EQUAL THE NUMBER OF MAPS.
	ORCE ACCOUNT ITEMS, SUCH AS PAINT STRIPING, SHOULD NOT BE ON
7	THE ESTIMATE UNLESS PROJECT HAS A FEDERAL AID PROJECT NUMBER

(IF APPLICABLE).
. COMPLETE THE COST BASED ESTIMATE QUANTITY BREAKDOWN
SUMMARY SHEET. STANDARD FORM IS ON WEB SITE LOCATION:
<pre>www.doh.dot.state.nc.us/preconstruct/highway/dsn_srvc/standard_list.html</pre>
GENERAL
. ARE THE WBS ELEMENTS CORRECTLY SHOWN ON ALL PLAN SHEETS?
THEY SHOULD BE IN NUMERICAL ORDER BEGINNING WITH THE SMALLES
WBS ELEMENT. MAP NUMBERS SHOULD BEGIN IN CONJUNCTION WITH
SMALLEST WBS ELEMENT AND CONTINUE IN AN ASCENDING ORDER.
. DOES PROJECT HAVE SEEDING AND MULCHING? IF SO, A SPECIAL
PROVISION (FOR THE MIX) FROM ROADSIDE ENVIRONMENTAL UNIT
SHOULD BE INCLUDED IN THE PACKAGE.
. IF THERE IS A REVISION OR ADDITION TO ANY QUANTITY, INFORM THE
CONTRACT OFFICE OF CHANGE. IF THERE IS A CHANGE IN THE NUMBER
OF PRIMARY OR SECONDARY SECTIONS, INFORM THE CONTRACT OFFICE.
. FIRST SHEET OF PLANS SHOULD SHOW COUNTY NAME.
. DO NOT SHOW PAVEMENT CONDITION RATING ON SUMMARY OF
QUANTITIES.
PLEASE PLACE A COPY OF ANY CORRESPONDENCE FROM ANY DESIGN
UNIT (i.e., TRAFFIC, PAVEMENT MANAGEMENT, GEOTECH, ETC.) IN WITH
THE RESURFACING PACKAGE DOCUMENTATION. EXAMPLES OF
CORRESPONDENCE ARE GEOTECHNICAL RECOMMENDATIONS, PAVEMENT
RECOMMENDATIONS AND SPECIAL DETAILS.
ALL PLAN SHEETS SHOULD INCLUDE A REFERENCE FOR SHEET NUMBERS
(SHEET OF) OR A TITLE BLOCK REFERENCING THE SHEET NUMBER
AND TOTAL NUMBER OF SHEETS.
PLEASE SUBMIT A DISKETTE CONTAINING THE ELECTRONIC FILES
(SUMMARY OF QUANTITIES, TYPICAL SECTIONS, RESURFACING PROGRAM
FILE, ETC.) WITH THE RESURFACING PACKAGE.
PLEASE INCLUDE A COPY OF ALL SPECIAL PROVISIONS WITH THE
RESURFACING PACKAGE. ANY CHANGES TO THE REGULAR PROJECT
SPECIAL PROVISIONS SHOULD BE SHOWN IN BOLD LETTERS OR MARKED
IN RED ON THE ORIGINAL. THE REGULAR PROJECT SPECIAL PROVISIONS
CAN BE ACCESSED FROM THE DIVISION OF HIGHWAYS WEB SITE.
. PLEASE CONTACT THE TRAFFIC CONTROL, MARKING & DELINEATION
SECTION PRIOR TO SUBMITTING THE RESURFACING PACKAGE IF THE
STANDARD TRAFFIC CONTROL SPECIAL PROVISIONS ARE NOT
APPLICABLE OR IF SPECIAL DETAILS/PLANS MAY BE REQUIRED.
TRAFFIC CONTROL & PAVEMENT MARKINGS
. THE TRAFFIC CONTROL SPECIAL PROVISIONS ARE R-1, R-2 OR R-3, AND R-4.
. CHOOSE EITHER R-2 OR R-3. NOT BOTH.
. MAKE ANY CHANGES NECESSARY TO SPECIAL PROVISIONS IN BOLD

LETTERS OR MARK CHANGES TO ORIGINAL IN RED.
INCLUDE PAVEMENT MARKINGS (PERMANENT AND TEMPORARY) AND
PAVEMENT MARKERS ON THE SUMMARY OF QUANTITIES.
PAVEMENT MARKINGS AND MARKERS SHOULD BE DETAILED ON THE
SUMMARY OF QUANTITIES BY COLOR (i.e., WHITE AND YELLOW
THERMOPLASTIC, CYAN AND RED MARKERS, ETC.)
THERMOPLASTIC CHARACTERS (RXR, ONLY, SCHOOL, ETC.) SHOULD BE
DENOTED ON THE SUMMARY OF QUANTITIES BY LOCATION AND SHOULD
REPRESENT THE NUMBER OF CHARACTERS REQUIRED TO SPELL OUT THE
MESSAGE. FOR EXAMPLE, A MAP WITH (2) SCHOOL AND (1) RXR
MESSAGES WILL SHOW QUANTITIES OF 12 EA. AND 2 EA., REPECTIVELY ON
THE SUMMARY OF QUANTITIES. A TOTAL OF 14 CHARACTERS WILL BE
SHOWN ON THE ESTIMATE FOR THIS MAP. THE "X" IN THE RXR MESSAGE
IS NOT A CHARACTER AND SHALL BE PAID FOR AS 16" THERMOPLASTIC.
THE TRANSVERSE BANDS SHOULD BE PAID FOR AS 24" THERMOPLASTIC.
PLANS PREPARED BY: